



◆ 技术参数 Technology parameters

型号 Type	公称推力(KN) Nominal push force(kn)	压缩室尺寸(长x宽x高)mm Dimension of compressed room LxWxHmm	包块尺寸(长x宽)mm Package block dimension LxWmm	生产效率(Kg/h) Production efficiency (Kg/h)	单次循环时间(s) Single cycle time(s)	功率(KW) Matched capacity(KW)
Y81PTZ-63	630	1500x750x2000	280x280	1000-1500	≤70	22
Y81PTZ-100X	1000	1500x750x2000	280x280	1300-1800	≤60	30
Y81PTZ-100A	1000	1500x1000x2000	300x300	2000-2500	≤65	37
Y81PTZ-100B	1000	2000x1000x2000	300x300	2500-3000	≤75	37
Y81PTZ-100C	1000	2000x1400x2000	350x350	3000-4000	≤75	44
Y81PTZ-100D	1000	2000x1750x2000	400x400	4000-4500	≤80	44
Y81PTZ-125A	1250	2000x1000x2000	300x300	3000-3500	≤80	44
Y81PTZ-125B	1250	2000x1750x2000	380x380	4500-5000	≤85	44
Y81PTZ-160A	1600	2500x1750x2000	400x400	6000-7000	≤100	74
Y81PTZ-160B	1600	3000x1750x2000	450x450	8000-10000	≤110	74

Q43系列鳄鱼式液压剪切机适用于金属回收公司、废钢厂、冶炼铸造企业对各种形状的型钢及各种金属结构进行冷态剪切，以加工合炉料。

Q43 series crocodile type metalshear is suitable to shear various shapes of profiled bar and metal structure parts at cold condition for metal recovery companies, waste steel factories, smelting and casting enterprises.

◆ 产品特点 Product Features

- 1、采用液压驱动，操作方便，维修简单。
 - 2、工作刀口长度：400mm, 600mm, 700mm, 800mm, 1000mm, 1200mm, 剪切力从63吨至500吨共8个等级。
 - 3、安装无须底脚螺丝，无电源的地方可用柴油机作动力。
- 1、Hydraulic driving, easy operation, easy maintenance.
 - 2、Work knife edge length: 400mm, 600mm, 700mm, 800mm, 1000mm, 1200mm, The shearing force has 8 classes from 63 tons to 400 tons. The shear with length over 700mm knife edge can be used to shear waste car.
 - 3、No requirements of foundation bolts for installation, the diesel may be used for driving at the place without power supplying.



◆ 技术参数 Technology parameters

型号 Type	最大剪切 Max. materia pressure(t)	刀口长度 Knife edge length(mm)	最大张口 Max opening mouth(mm)	每分钟可剪切次数 Shearing time per min	主要被剪材料尺寸 Dimension of main sheared material	机器总功率 Total power of machine(kw)	操作方式 Operationa method
Q43-63	63	400	200	10-14	30 x 30, φ35	7.5	人工送料，手动或自动 Manual feeding manual or automatic
		600	600				
		800	800				
Q43-100	100	600	280	10-14	40 x 40, φ45	7.5	
Q43-100A	100	800	320	10-14	40 x 40, φ50	11	
Q43-120	120	600	280	10-13	45 x 45, φ50	15	
Q43-130	130	600	320	10-13	45 x 45, φ50	18.5	
Q43-160	160	700	320	10-12	55 x 55, φ63	18.5	
Q43-160A	160	800	350	10-12	55 x 55, φ63	18.5	
Q43-200	200	800	380	9-12	60 x 60, φ65	22	
Q43-250	250	1000	450	8-12	70 x 70, φ75	30	
Q43-315	315	1200	520	8-11	80 x 80, φ85	37	
Q43-400	400	1500	660	8-11	90 x 90, φ85	44	
Q43-500	500	1600	690	6-10	小轿车, 120	60	