

用于各类生产和生活用废钢各种有色金属(不锈钢、铜等)直接切成所需大小。加料室尺寸大, 适合广泛的材料采用PLC全自动控制。高效率, 随时可以调整剪切长度。

For all kinds of production and life use scrap non-ferrous metal (stainless steel, copper, etc.) directly cut into the required size. Room size, suitable for a wide range of materials. PLC automatic control. High efficiency, shear length can be adjusted at any time



### ◆ 技术参数 Technology parameters

型号 Type	最大剪切力(吨) Max shear pressure	料箱尺寸(mm) Feeding size	开口高度(mm) Opening Highly	刀口长度(mm) Knife edge length	产量(吨/小时) Production	剪切频率(次/分) Shear rate	主电机(kw) Motor
Q91Y-315	3150	3000 × 1200 × 800	400	1200	4-8	3-4	90
Q91Y-400	4000	5000 × 1600 × 800	400	1600	7-10		90
Q91Y-500	5000	6000 × 1600 × 800	500	1600	10-15		135
Q91Y-630	6300	8000 × 1800 × 900	500	1800	13-18		225
Q91Y-800	8000	8000 × 1800 × 1000	600	1800	15-20		270
Q91Y-1000	10000	8000 × 2000 × 1200	700	2000	18-25		360

PSX系列废钢破碎机, 用于加工报废汽车车体、马口铁类、旧家电、自行车、空罐等下等废料成为上级的制钢原料。通过本机不断粉碎, 涂膜, 提高体积比重, 投电炉时防止爆炸, 在一定状态下提升溶解率等, 满足钢厂“精料入炉”的要求。

PSX series scrap steel smashing assembly line, is for processing scrap car bodies, tinplate class, old electrical appliances, bicycles, cans and other waste materials inferior to make it as superior steel materials. Constantly crushed by the machine, go coating to improve the peoporition of volume to prevent explosion cast furnace, at a certain state to improve the dissolution rate, etc. to meet the mills' fine material into the furnace "requirement".



### ◆ 技术参数 Technology parameters

型号 Type	料口宽度 (mm) Width of feed opening	主机功率 (HP) Main power	生产能力 (T/H) Productivity
PSX-90	1000	900(120)	2-3
PSX-160	1200	160(212)	4-6
PSX-400	1400	400(535)	6-10
PSX-500	1600	500(670)	12-18
PSX-700	2200	700(1000)	15-20
PSX-900		900(1200)	20-25
PSX-1200		1200(1600)	25-30
PSX-1500	2500	1500(2000)	30-50
PSX-2250		2250(3000)	50-70

