

Y81F翻包金属打包机

Y81F Turn Metal Baler

Y81系列金属液压打包机适用于炼钢厂,回收加工行业及有色、黑色金属冶炼行业。可将各种金属边角料、钢刨花、废钢、废铝、废铜等挤压成长方形、圆柱体、八角形体等各种形状的合格炉料，以降低运输和冶炼成本。

Y81 series metal hydraulic balers are suitable for steelmaking plants, recycling processing industries and non-ferrous and ferrous metal smelting industries. It can extrude all kinds of metal leftovers, steel shavings, scrap steel, scrap aluminum, scrap copper, etc. into qualified charge of various shapes such as rectangle, cylinder, octagon, etc., so as to reduce transportation and smelting costs.

型号 Type	公称推力 (kN) Nominal push (kn)	压缩室尺寸 (长×宽×高) mm Compression chamber size (L x W x H) mm	包块尺寸 (长×宽) mm Baler size (L x W) mm	生产效率 (Kg/h) Production efficiency (Kg/h)	单次循环时间 (s) Single cycle time (s)	功率 (KW) Power (KW)	出包/操作方式 Baler coming out/operation mode
Y81F-125A	1250	1200 × 700 × 600	300 × 300	1200-1800	≤ 110	15	
Y81F-135	1350	1400 × 900 × 700	350 × 350	1800-2200	≤ 120	22	
Y81F-160	1600	1400 × 900 × 800	350 × 350	2000-3000	≤ 150	22	
Y81F-160B	1600	1600 × 1200 × 800	400 × 400	2000-4000	≤ 150	30	
Y81F-200B	2000	1800 × 1200 × 900	500 × 500	3000-5000	≤ 160	44	
Y81F-250B	2500	2000 × 1400 × 900	500 × 500	5000-6300	≤ 160	44	
Y81F-250D	2500	2500 × 2000 × 1200	500 × 500	5500-6500	≤ 160	60	翻包，手动/全自动操作
Y81F-315B	3150	2000 × 1750 × 1200	600 × 600	5000-7000	≤ 160	74	Turn
Y81F-315G	3150	3500 × 3000 × 1300	700 × 700	10000-15000	≤ 160	90	Manual/PLC operation
Y81F-400B	4000	2500 × 2000 × 1200	600 × 600	7500-9000	≤ 180	90	
Y81F-400C	4000	3000 × 2500 × 1300	600 × 600	8000-10000	≤ 180	135	
Y81F-400D	4000	3500 × 3000 × 1200	700 × 700	9000-12000	≤ 190	135	
Y81F-500C	5000	3500 × 3000 × 1300	700 × 700	15000-20000	≤ 180	110	
Y81F-630A	6300	3500 × 3000 × 1300	700 × 700	15000-20000	≤ 180	165	
Y81F-800B	8000	3500 × 3000 × 1300	700 × 700	18000-22000	≤ 180	165	
Y81F-1000B	10000	4000 × 3000 × 1300	800 × 800	25000-30000	≤ 180	220	



Y81T侧推包金属打包机

Y81T Side Push Metal Baler

型号 Type	公称推力 (KN) Nominal push force(kn)	压缩室尺寸 (长 X 宽 X 高)mm Dimension of compressed room (L x W x H)mm	包块尺寸 (长 x 宽)mm Package block dimension (L x W)mm	生产效率 (Kg/h) Production efficiency (Kg/h)	单次循环时间 (s) Single cycle time(s)	功率 (KW) Matched capacity(KW)	出包操作方式 Bag coming out/ operational method
Y81T-100	1000	1000x700x 550	250x 250	1200~1500	≤85	11	
Y81T-125A	1250	1200x700 x600	300 x 30	1200~1800	≤110	15	
Y81T-125Y	1250	1200x700x600	φ 200 圆形	1200~1700	≤115	15	
Y81T-135	1350	1400x900x700	350x350	1800~2200	≤120	22	
Y81T-160	1600	1400x900 x800	350x350	2000~3000	≤150	22	
Y81T-160A	1600	1600x1000x800	400x400	2000~3500	≤150	22	
Y81T-160B	1600	1600x1200 x800	400x400	2000~4000	≤150	30	
Y81T-200A	2000	1600x1200 x800	450x450	2500~4500	≤160	30、37	
Y81T-200B	2000	1800x1200 x900	500x500	3000~5000	≤160	37、44	
Y81T-200C	2000	2000x1400 x900	500x500	3500~5500	≤160	44	
Y81T-250A	2500	1800x1200x900	500x500	4000~6300	≤160	44、60	推包，手动 / 全自动操作
Y81T-250B	2500	2000x1400 x900	500x500	5000~6300	≤160	44、60、74	Side push
Y81T-250C	2500	2000x1750x1200	500x500	5500~6500	≤160	60	Manual/PLC operation
Y81T-250D	2500	2500x2000x1200	500x500	5500~6500	≤160	60、74	
Y81T-250E	2500	3000x2500x1200	500x500	5500~6500	≤160	60、74	
Y81T-315A	3150	2000x1400x1200	500x500	5000~6500	≤160	60、74	
Y81T-315B	3150	2000x1750x1200	600x600	5000~7000	≤160	60、74	
Y81T-315C	3150	2500x2000x1200	600x600	6000~7500	≤180	74	
Y81T-315D	3150	3000x2500x1300	700x700	7000~8000	≤180	90	
Y81T-400A	4000	2000x1600x1200	600x600	5000~7000	≤160	74	
Y81T-400B	4000	2500x2000x1200	600x600	7500~9000	≤180	90	
Y81T-400C	4000	3000x2000x1300	700x700	8000~10000	≤180	90	
Y81T-400D	4000	3000x2500x1300	700x700	9000~12000	≤190	135	



油缸
Oil cylinder



液压站
Hydraulic station



电气柜
Electrical cabinet



激光智能检测
Laser intelligent detection



无人操作
Unmanned operation



遥控器
Remote control



远程模块
Remote module



维修售后远程协助
Repair and after-sales remote assistance

Y81Q前出包金属打包机

Y81Q Front Push Metal Baler

- 1、各种机型均采用液压驱动。可选择手动或PLC自动控制操作。

2、安装无须底脚螺丝，在无电源的地方可配用柴油机作动力。

3、出包方式有翻包、侧推包、前出包三种方式。

4、挤压力从125吨至1000吨有多个等级，生产效率从1.2吨/小时至30吨/小时。

5、加料箱尺寸和包块形状尺寸可根据用户原料规格设计定制，可选配加料箱两侧带刀片。
- 1、The hydraulic driving is adopted for all types of machines.The manual or PLC automatic control operations are optional.

2、No need foundation bolts for installation.The diesel be equipped as power at the place without power supplying.

3、Bale out type:Turn over ,side push,front push.

4、There are multiple levels of extrusion force from 125 tons to 1000 tons, and production efficiency from 1.2 tons/hour to 30 tons/hour.

5、The chamber box size and bale size can be customized clients' requirements, can choose blades for the chamber box.

型号 Type	公称推力 (KN) Nominal push force(kn)	压缩室尺寸 (长 X 宽 X 高)mm Dimension of compressed room (LxWxH)mm	包块尺寸 (长 x 宽) mm Package block dimension (L xW)mm	生产效率 (Kg/h) Production efficiency (Kg/h)	单次循环时间 (s) Single cycle time(s)	功率 (KW) Matched capacity(KW)	出包操作方式 Bag coming out/ operational method
Y81Q-63	630	600 x 500x 500	500x220	600-1000	≤75	7.5	
Y81Q-100	1000	1100 x 600 x 550	600x220	1000-1800	≤85	11	
Y81Q-135A	1350	1400 X 600x 600	600x240	1500-2800	≤80	22	前出包，手动 / 全自动操作
Y81Q-135B	1350	1100 x 600 x 600	600X240	1200-1700	≤100	15、18.5	Front push
Y81Q-160	1600	1450 x 600x 600	600x300	2000-3000	≤110	22	Manual/PLC operation
Y81Q-200	1600	1450 x 700 x 600	700X300	2800-3500	≤110	30	
Y81Q-250	1600	1800 x 900 x 700	900x350	4500-6500	≤130	44	



Y81系列机器照片&案例

Y81 series machine photos & cases



Y81系列机器照片&案例

Y81 series machine photos & cases

